AMENDMENTS TO THE CLAIMS

- (Currently Amended) A method of providing access to services across a computer network, comprising the step of:
 - generating an access request by a requesting network access device through which an end user device can obtain access to network resources, said access request comprising including a requesting network access device description and a plurality of service requests indicative of computer services for which the requesting network access device requests provisioning;
 - wherein the requesting network access device description includes one or more of: a requesting network access device vendor, a requesting network access device type, a requesting network access device version and a requesting network access device physical location; and

forwarding said access request for authentication and authorization.

- (Original) A method according to Claim 1 in which the access request is a RADIUS packet, the service requests being defined by information contained within Vendor-Specific Attribute (VSA) blocks in the said packet.
- (Currently Amended) A method according to Claim 2 in which each said block contains a requesting network access device-type identifier and a service-request identifier.
- (Original) A method according to Claim 2 in which the packet is a RADIUS-compliant authentication request packet.
- (Canceled)
- (Original) A method according to Claim 1 in which the service requests include a request for a particular service level.
- (Original) A method according to Claim 1 in which a policy is applied to the access request to determine whether access will be allowed, and if so for what services.

- (Currently Amended) A method according to Claim 1 in which [[a]] <u>said</u> network resources are provisioned in dependence upon the access request.
- (Original) A method according to Claim 1 in which the steps of receiving and applying are performed by an access-control server or an Authentication, Authorization and Audit (AAA) server.
- (Original) A method according to Claim 9 in which the access-control server uses the access request to select among multiple services that are specified for a particular device.
- (Currently Amended) A network device arranged to provide access to services across a computer network, comprising:
 - means for generating an access request by a requesting network access device through
 which an end user device can obtain access to network resources, said access
 request comprising including a requesting network device description and a
 plurality of service requests indicative of computer services for which the
 requesting network access device requests provisioning;
 - wherein the device description includes one or more of; a <u>requesting network access</u> device vendor, <u>a requesting network access</u> device type, <u>a requesting network access</u> device eversion and <u>a requesting network access device</u> physical location; and
 - means for forwarding said access request for authentication and authorization.
- (Original) A network device according to Claim 11 including means to generate RADIUS-compliant packets, the service requests being defined by information contained within Vendor-Specific Attribute (VSA) blocks in this said packet.
- 13. (Currently Amended) A network device, comprising: a network interface capable of being coupled to a requesting network access device and a computer network and for sending to the network access requests, a processor and a computer-readable storage medium having one or more stored sequences of instructions which, when executed, cause the processor to perform the steps of:

- generating an access request by the requesting network access device through which an end user device can obtain access to network resources for forwarding via the network interface, said access request comprising including a requesting network access device description and a plurality of service requests indicative of computer services for which the requesting network access device requests provisioning;
- wherein the requesting network access device description includes one or more of: a requesting network access device vendor, a requesting network access device type, a requesting network access device version and a requesting network access device physical location; and

forwarding said access request for authentication and authorization.

- 14. (Original) A network device according to Claim 13 in which the access request is received as a RADIUS packet, the service requests being defined by information contained within Vendor-Specific Attribute (VSA) blocks in this said packet.
- (Currently Amended) A network device according to Claim 14 in which each said block contains a requesting network access device-type identifier and a service-request identifier.
- (Original) A network device according to Claim 14 in which the packet is a RADIUScompliant authentication request packet.
- 17. (Canceled)
- (Original) A network device according to Claim 13 in which the service requests include a request for a particular service level.
- (Currently Amended) A computer system comprising an access-control server for controlling access to resources on the network when requested by requesting network access devices, the access-control server being arranged:

(a) to receive an access request from a network by a requesting network access device through which an end user device can obtain access to network resources, said access request comprising including a requesting network access device description and a plurality of service requests indicative of computer services for which the requesting network access device requests provisioning;

wherein the <u>requesting network access</u> device description includes one or more of: a <u>requesting network access</u> device vendor, a <u>requesting network</u> <u>access</u> device type, a <u>requesting network access</u> device version and a requesting network access device physical location; and

- (b) to apply a policy to the access request to determine whether access will be allowed, and if so for what services.
- (Original) A computer system according to Claim 19 in which the access control server
 instructs the provisioning of network resources in dependence upon the access request.
- (Original) A computer system according to Claim 19 in which the access-control server is an Authentication, Authorization and Audit (AAA) server.
- (Original) A computer system according to Claim 19 in which the access-control server
 uses the access request to select among multiple services that are specified for a particular
 device.
- 23. (Currently Amended) A computer-readable storage medium storing a sequence of instructions which, when executed by one or more processors, causes said processor or processors to perform the steps of:

generating an access request by a requesting network access device through which an end user device can obtain access to network resources for access to resources on a computer network, said access comprising including a requesting network access device description and a plurality of service requests indicative of computer services for which the requesting network access device requests provisioning; wherein the requesting network access device description includes one or more of; a requesting network access device vendor, a requesting network access device

type, a requesting network access device version and a requesting network access device physical location; and

forwarding said access request for authentication and authorization.

- 24. (Previously Presented) A computer-readable storage medium according to Claim 23 further including instructions for generating a RADIUS packet, the service requests being defined by information contained within Vendor-Specific Attribute (VSA) blocks in said packet.
- (Currently Amended) A computer-readable storage medium according to Claim 24
 further including instructions for creating within each said block a requesting network
 access device-type identifier and a service-request identifier.
- (Previously Presented) A computer-readable storage medium according to Claim 24 in which the generated packet is a RADIUS-compliant authentication request packet.
- (Currently Amended) A computer-readable storage medium according to Claim 23, in
 which the <u>requesting network access</u> device description includes one or more of device
 vendor, device type, device version, physical location.
- (Previously Presented) A computer-readable storage medium according to Claim 23, in which service requests include a request for a particular service level.
- 29. (Currently Amended) A network device as claimed in claim 11 or claim 13 comprising a requesting network access device which controls end-user device access to a network, and which requests services on behalf of one or more said end-user devices.
- (Currently Amended) A network device as claimed in claim 11 or claim 13 in which said requesting network access device requests services for its own use.